

# Technical Datasheet

		EN ISO 13485 certified
<b>Article - No:</b>	<b>04-212-1005</b>	<b>Revision: 2</b>
<b>Remarks</b>	<b>piercable cap</b>	<b>single use only</b>

## Specification

<b>Product</b>	Microcentrifuge tube PP, 1,5ml, attached cap, blue graduated, with writing area, max. RCF 18.000g, autoclavable up to 121°C, CE/IVD
<b>Classification</b>	CE/IVD
<b>Dimensions</b>	tube:
	outer diameter 13,00 mm (+/- 0,2 mm)
	inner diameter: 10,80 mm (+/- 0,2 mm)
	height: 39,00 mm (+/- 0,2 mm)
	cap:
	length 20,00 mm (+/- 0,2 mm)
	width: 13,20 mm (+/- 0,2 mm)
	total height (tube and cap): 39,90 mm (+/- 0,2 mm)
<b>Colour</b>	blue
<b>Graduation</b>	grad., writ. area
<b>Nominal Capacity</b>	1,5ml
<b>Material Characteristics</b>	polypropylene (PP)
<b>Temperature range</b>	-70°C - 121°C
<b>Autoclavability</b>	autocl. up to 121°C
<b>Centrifugation</b>	max. RCF 18.000g
<b>Product Characteristics</b>	biologically inert
	physiologically harmless
	no heavy metals according to EC/94/62
<b>Purity Grade</b>	manufactured in clean rooms of ISO Class 8 or better (DIN EN ISO 14644-1)
<b>Packaging</b>	pcs per bag: 1.000
	pcs per carton: 8.000
	pcs per pallet: 176.000
<b>Storage</b>	dry condition: 40%-60% rel. humidity
	bags / cases orig. closed

# Technical Datasheet

Date: 22.06.20

Page 2 of 2

	storage temp. +2°C to max. +30°C
	pal. not stackable
<b>Approved by nerbe plus quality department</b>	

